Url: https://www.urp.cnr.it/235577-2024

VERBALE DI COLLAUDO

Il sottoscritto Roati Giacomo Responsabile Unico del Progetto della procedura di acquisto di beni, come da ordine MEPA num.4536844 Prot. Cnr-Ino num.316953 del 12/09/2024 (rif. Interno n.264/SE) con la ditta Optoprim CIG: B28BEA230E CUP: B93C22000620006

DICHIARA

- di aver effettuato in data odierna il collaudo dei beni pervenuti e riportati dalla fattura (Saldo) num.2929 del 20/11/2024 di importo pari a 24.071,82 Euro; rilevando la conformità con quanto ordinato ed il regolare funzionamento.

- di procedere all'inventario dei beni come segue:

Descrizione bene	Ubicazione	Affidatario	Importo	Codice bene	Firma affidatario
Reconfigurable Servo designed for low-noise servo control of lasers and other experimental systems, containing a tunable PI2D loop filter for tight locking to an error signal, with specifications including:- full PID loop filter with 10 MHz bandwidth- internal ramp generator- auxiliary servo channel for long-term drift or PZT control- full user control over the loop-filter parameters- auto relock functionality- ramp centering servo signal offset capability - internal power supply to operate the device from 230V AC line voltage	FIRENZE - Polo Sesto - Dip. Fisica - Lab. st. 86	Tanzi Luca	8.023,94€	111.005-1076150-000	
Reconfigurable Servo designed for low-noise servo control of lasers and other experimental systems, containing a tunable PI2D loop filter for tight locking to an error signal, with specifications including:- full PID loop filter with 10 MHz bandwidth- internal ramp generator- auxiliary servo channel for long-term drift or PZT control- full user control over the loop-filter parameters- auto relock functionality- ramp centering servo signal offset capability - internal power supply to operate the device from 230V AC line voltage	FIRENZE - Polo Sesto - Dip. Fisica - Lab. st. 86	Tanzi Luca	8.023,94€	111.005-1076151-000	
Reconfigurable Servo designed for low-noise servo control of lasers and other experimental systems, containing a tunable PI2D loop filter for tight locking to an error signal, with specifications including:- full PID loop filter with 10 MHz bandwidth- internal ramp generator- auxiliary servo channel for long-term drift or PZT control- full user control over the loop-filter parameters- auto relock functionality- ramp centering servo signal offset capability - internal power supply to operate the device from 230V AC line voltage	FIRENZE - Polo Sesto - Dip. Fisica - Lab. st. 86	Tanzi Luca	8.023,94€	111.005-1076152-000	

Categoria Inventariale: **strumentazioni scientifiche PNRR**

Progetto: **CN00000013 National Centre for HPC, Big Data and Quantum Computing** ***Istituzionale***

Sesto Fiorentino, 11 dicembre 2024

Il Responsabile Unico del Progetto

CNR-INO ISTITUTO NAZIONALE DI OTTICA CONSIGLIO NAZIONALE DELLE RICERCHE
Via Nello Carrara, 1 – 50019 Sesto Fiorentino
P.IVA 02118311006 - C.F. 80054330586 - WWW.INO.CNR.IT - PROTOCOLLO.INO@PEC.CNR.IT